

| DRIVER DETAILS | |
|------------------|-------------------|
| NAME | masaki honda |
| DATE | 2011/8/25/26 |
| EVENT | JMRCA Sportsclass |
| WEATHER | |
| RESULT | 6th |
| FASTEST LAP TIME | |

| NOTES | |
|-------------|--|
| U4610X2 USE | |
| U480T USE | |



| CHASSIS AND ELECTRICS | |
|-----------------------|--|
| CHASSIS | Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/> |
| TOP DECK | 2.0mm <input type="checkbox"/> 2.5mm <input checked="" type="checkbox"/> 3.0mm <input type="checkbox"/> 4.0mm <input type="checkbox"/> |
| BODYSHELL | ALEX M6 highspeed |
| WING | PF |
| E.S.C | HOBBYWING XR-10 |
| SERVO | SANWA P6S-LH |
| RECEIVER | SANWA RX-482 |
| CELLS | |

| MOTOR AND GEARING | |
|-------------------|--|
| MOTOR | R1 WURKS |
| ROTOR DIAMETER | 12.5MM |
| TIMING | 0 |
| GEAR PITCH | 48DP <input type="checkbox"/> 64DP <input checked="" type="checkbox"/> |
| SPUR SIZE | 106 |
| PINION SIZE | 35 |

| TRACK CONDITIONS | |
|------------------|--|
| GRIP LEVEL | High <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Low <input type="checkbox"/> |
| TYPE | Tight <input checked="" type="checkbox"/> Open <input type="checkbox"/> Mixed <input type="checkbox"/> |
| SURFACE | Carpet <input type="checkbox"/> Tarmac <input checked="" type="checkbox"/> |
| CONDITION | Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> |
| TEMPERATURE | °C °F |
| VENUE | Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> |

| WHEELS, TYRES AND INSERTS | |
|---------------------------|---|
| WHEELS | YOKOMO(control) |
| TYRES | 50REX40(control) |
| INSERTS | bomber red(control) |
| TYRE ADDITIVE | mightv3(control) |
| ADDITIVE TIME | Front 1 Minutes Rear 1 Minutes |
| TYRE WARMERS | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Temp 45 °C Time 1 Minutes |

FRONT

Diff Oil cTs

Spool Gear Diff

1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm
5 Dot - 1.5mm

Washers 0.5mm

Washers 2mm
Washers 3 mm

4° Yoke 6° Yoke

SERVO SAVER Yes No

Washers 2mm

12mm
13mm
14mm

Alloy Steel Double Joint

Narrow Medium (kit)

Washers 1mm

Line In Shims 0mm
Line Out 0mm

Dropover 10mm
On 10mm Block
Ride Height 4.4mm
Camber 2°
Toe OUT
Pivot Block Strap

44.2 (0)
43.5 44.2 45.0

Cap Type Vented Sealed Emulsion

Oil AXDN35cTs

Spring AXDN2.5

Piston NORMAL

Drilled Yes No

Drilled piston Hole Sizemm

Shock Length (X)mm

Rebound%

Peripheral
Damping Yes No

REAR

Diff Oil 7500 cTs

0 Dot - 1.0mm
1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm

Washers 2mm

Washers 1mm

Washers 2mm

WheelBase Short Middle Long

Alloy Steel

Line In Shims 0mm
Line Out 0mm

Dropover 1mm
On 10mm Block
Ride Height 4.6mm
Camber 2°
Pivot Block Strap

48.1
44.2 45.5 46.1

Cap Type Vented Sealed Emulsion

Oil AXDN35cTs

Spring AXDN2.5

Piston NORMAL

Drilled Yes No

Drilled piston Hole Sizemm

Shock Length (X)mm

Rebound%

Peripheral
Damping Yes No

| DRIVER DETAILS | |
|------------------|-------------------|
| NAME | makoto oda |
| DATE | 2011/8/25/26 |
| EVENT | JMRCA Sportsclass |
| WEATHER | |
| RESULT | 4th |
| FASTEST LAP TIME | |

NOTES

U4610X2 USE
U4807 USE



| CHASSIS AND ELECTRICS | |
|-----------------------|--|
| CHASSIS | Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/> |
| TOP DECK | 2.0mm <input type="checkbox"/> 2.5mm <input checked="" type="checkbox"/> 3.0mm <input type="checkbox"/> 4.0mm <input type="checkbox"/> |
| BODYSHELL | ALEX M6 highspeed |
| WING | rc mission |
| E.S.C | HOBBYWING XR-10 |
| SERVO | SANWA PG5-LH |
| RECEIVER | SANWA RX-482 |
| CELLS | |

| MOTOR AND GEARING | |
|-------------------|--|
| MOTOR | R1 WURKS |
| ROTOR DIAMETER | 12.5MM |
| TIMING | 0 |
| GEAR PITCH | 48DP <input type="checkbox"/> 64DP <input checked="" type="checkbox"/> |
| SPUR SIZE | 106 |
| PINION SIZE | 35 |

| TRACK CONDITIONS | |
|------------------|--|
| GRIP LEVEL | High <input checked="" type="checkbox"/> Medium <input type="checkbox"/> Low <input type="checkbox"/> |
| TYPE | Tight <input checked="" type="checkbox"/> Open <input type="checkbox"/> Mixed <input type="checkbox"/> |
| SURFACE | Carpet <input type="checkbox"/> Tarmac <input checked="" type="checkbox"/> |
| CONDITION | Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/> |
| TEMPERATURE | °C _____ °F _____ |
| VENUE | Indoor <input checked="" type="checkbox"/> Outdoor <input type="checkbox"/> |

| WHEELS, TYRES AND INSERTS | |
|---------------------------|---|
| WHEELS | YOKOMO(control) |
| TYRES | SOREX40(control) |
| INSERTS | bomber red(control) |
| TYRE ADDITIVE | mighty3(control) |
| ADDITIVE TIME | Front Minutes Rear Minutes |
| TYRE WARMERS | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Temp 40 °C Time Minutes |

FRONT

| | | | |
|--|---|--|--|
| <p>Spool <input checked="" type="checkbox"/> Gear Diff <input type="checkbox"/></p> <p>Diff Oil cTs</p> | <p>1 Dot - 1.1mm 2 Dot - 1.2mm 3 Dot - 1.3mm 4 Dot - 1.4mm 5 Dot - 1.5mm</p> | <p>Line In <input checked="" type="checkbox"/> Shims 0mm Line Out <input type="checkbox"/> 0mm</p> | <p>Drop.....mm On 10mm Block <input type="checkbox"/> Ride Height 4.4mm Camber 2° Toe.....OUT 1° Pivot Block Strap <input type="checkbox"/></p> <p>43.5 <input type="checkbox"/> 44.2 <input checked="" type="checkbox"/> 46.0 <input type="checkbox"/></p> |
| <p>Washers 2mm Washers.....3mm</p> | <p>Washers 0.5mm</p> | <p>Shims 0mm</p> | <p>Cap Type Vented <input type="checkbox"/> Sealed <input type="checkbox"/> Emulsion <input type="checkbox"/> Oil..... AXDN37.5cTs Spring..... AXDN2.5 Piston..... NORMAL Drilled Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Drilled piston Hole Size.....mm Shock Length (X).....mm Rebound%</p> |
| <p>4° Yoke <input checked="" type="checkbox"/> 6° Yoke <input type="checkbox"/></p> <p>SERVO SAVER Yes <input type="checkbox"/> No <input checked="" type="checkbox"/></p> | <p>Washers 2mm</p> <p>12mm <input type="checkbox"/> 13mm <input type="checkbox"/> 14mm <input type="checkbox"/></p> | <p>Washers 1mm</p> | <p>Peripheral Damping Yes <input type="checkbox"/> No <input checked="" type="checkbox"/></p> |
| <p>Alloy <input type="checkbox"/> Steel <input type="checkbox"/> Double Joint <input checked="" type="checkbox"/></p> | <p>Narrow <input type="checkbox"/> Medium (kit) <input checked="" type="checkbox"/></p> | | |

REAR

| | | | |
|---|--|--|--|
| <p>Diff Oil 1000 cTs</p> | <p>0 Dot - 1.0mm 1 Dot - 1.1mm 2 Dot - 1.2mm 3 Dot - 1.3mm 4 Dot - 1.4mm</p> | <p>Medium <input checked="" type="checkbox"/> Wide (kit) <input type="checkbox"/></p> | <p>Drop.....mm On 10mm Block <input type="checkbox"/> Ride Height 4.6mm Camber 2° Pivot Block Strap <input type="checkbox"/></p> <p>44.2 <input type="checkbox"/> 45.5 <input checked="" type="checkbox"/> 46.1 <input type="checkbox"/></p> |
| <p>Washers 2mm</p> | <p>Washers 1mm</p> | <p>WheelBase Short <input checked="" type="checkbox"/> Middle <input type="checkbox"/> Long <input type="checkbox"/></p> | <p>Cap Type Vented <input type="checkbox"/> Sealed <input type="checkbox"/> Emulsion <input type="checkbox"/> Oil..... AXDN37.5cTs Spring..... AXDN2.5 Piston..... NORMAL Drilled Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Drilled piston Hole Size.....mm Shock Length (X).....mm Rebound%</p> |
| <p>Alloy <input type="checkbox"/> Steel <input checked="" type="checkbox"/></p> | | | <p>Peripheral Damping Yes <input type="checkbox"/> No <input checked="" type="checkbox"/></p> |