

**DRIVER DETAILS**

NAME \_\_\_\_\_  
 DATE \_\_\_\_\_  
 EVENT \_\_\_\_\_  
 WEATHER \_\_\_\_\_  
 RESULT \_\_\_\_\_  
 FASTEST LAP TIME \_\_\_\_\_

**NOTES**

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



**CHASSIS AND ELECTRICS**

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL \_\_\_\_\_  
 WING \_\_\_\_\_  
 E.S.C \_\_\_\_\_  
 SERVO \_\_\_\_\_  
 RECEIVER \_\_\_\_\_  
 CELLS \_\_\_\_\_

**MOTOR AND GEARING**

MOTOR \_\_\_\_\_  
 ROTOR DIAMETER \_\_\_\_\_  
 TIMING \_\_\_\_\_  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE \_\_\_\_\_  
 PINION SIZE \_\_\_\_\_

**TRACK CONDITIONS**

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE \_\_\_\_\_ °C \_\_\_\_\_ °F  
 VENUE Indoor  Outdoor

**WHEELS, TYRES AND INSERTS**

WHEELS \_\_\_\_\_  
 TYRES \_\_\_\_\_  
 INSERTS \_\_\_\_\_  
 TYRE ADDITIVE \_\_\_\_\_  
 ADDITIVE TIME Front Minutes Rear Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

**FRONT**

Spool  
 Gear Diff

Diff Oil ..... cTs

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Line In   
Line Out

Droop.....mm  
 On 10mm Block   
 Ride Height .....mm  
 Camber.....°  
 Toe.....°  
 Pivot Block Strap

44.2  
43.5 44.2 46.0

Washers .....mm

Washers .....mm

Washers .....mm

Washers .....mm

12mm   
13mm   
14mm

Cap Type Vented  Sealed  Emulsion   
 Oil.....cTs  
 Spring.....  
 Piston.....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping  
Yes   
No

Alloy  Steel  Double Joint

Narrow   
Medium (kit)

Washers .....mm

**REAR**

Diff Oil ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm

Medium  
 Wide (kit)

Droop.....mm  
 On 10mm Block   
 Ride Height .....mm  
 Camber.....°  
 Pivot Block Strap

48.1  
44.2 45.5 46.1

Washers .....mm

Washers .....mm

Washers .....mm

Washers .....mm

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove

WheelBase  
 Short  
 Middle  
 Long

Line In   
Line Out

Cap Type Vented  Sealed  Emulsion   
 Oil.....cTs  
 Spring.....  
 Piston.....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping  
Yes   
No

Alloy  Steel